

TYRES

Product group	Tyres
Item number	14826055
Valid tyre size	600 / 70 R 30
LI / SI / PR	158 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION XXL





Notes and features

- The Traxion XXL was developed for tractors with an engine performance above 160 hp.
- Its special tread pattern and flexible casing provide a large contact area and thus even ground pressure distribution.
- The large tyre volume enables a high load capacity at low inflation pressure.
- In field applications, the tyre offers excellent traction.
- In transport journeys, it distinguishes itself through high ride comfort and safety at speeds up to 70 km/h.



Technical Informations

Item number	14826055
EAN	8714692326967
Valid tyre size	600 / 70 R 30
LI / SI / PR	158 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION XXL
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	198,99
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	630
Outer diameter of tyre [mm].	1590
Stat. radius (SLR) [mm]	725
Rolling circumference [mm].	4750
Tread depth (mm)	53,1
Tyre capacity 75% [ltr.]	430
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.