

TYRES

Product group	Tyres
Item number	14826225
Valid tyre size	620 / 70 R 42
LI / SI / PR	166 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION +



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.

Technical Informations

Item number	14826225
EAN	8714692276996
Valid tyre size	620 / 70 R 42
LI / SI / PR	166 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION +
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	267,24
Recommended rim size	DW20B
Permitted rim size	W18L, DW18L
Maximum air pressure [bar].	2,40
Section width (mm)	625
Outer diameter of tyre [mm].	1930
Stat. radius (SLR) [mm]	880
Rolling circumference [mm].	5780
Tread depth (mm)	54,0
Tyre capacity 75% [ltr.]	585
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		2,40	