

TYRES

Product group	Tyres
Item number	14826332
Valid tyre size	280 / 85 R 24
LI / SI / PR	115 A8 / 115 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.

Technical Informations

Item number	14826332
EAN	8714692244551
Valid tyre size	280 / 85 R 24
LI / SI / PR	115 A8 / 115 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	46,88
Recommended rim size	W10
Permitted rim size	W9
Maximum air pressure [bar].	1,60
Section width (mm)	295
Outer diameter of tyre [mm].	1090
Stat. radius (SLR) [mm]	520
Rolling circumference [mm].	3275
Tread depth (mm)	37,0
Tyre capacity 75% [ltr.]	75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
115 A8	1215	40		1,60	
115 B	1215	50		1,60	