Bohnenkamp Moving Professionals

14.11.2024

TYRES

Product group	Tyres
Item number	14826368
Valid tyre size	340 / 85 R 28
LI / SI / PR	127 A8 / 127 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85



Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	14826368
EAN	8714692109799
Valid tyre size	340 / 85 R 28
Alternative size 1	13.6R28
LI / SI / PR	127 A8 / 127 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	65,77
Recommended rim size	W12
Permitted rim size	W11, W12L
Maximum air pressure [bar].	1,60
Section width (mm)	360
Outer diameter of tyre [mm].	1290
Stat. radius (SLR) [mm]	610
Rolling circumference [mm].	3870
Tread depth (mm)	41,0
Tyre capacity 75% [ltr.]	135
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 A8	1750	40		1,60	
127 B	1750	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.