

## **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 14826380       |
| Valid tyre size | 380 / 85 R 30  |
| LI / SI / PR    | 135 A8 / 135 B |
| TL/TT           | TL             |
| Brand           | Vredestein     |
| Tread pattern   | TRAXION 85 II  |





## Notes and features

- The Traxion 85 II is a standard radial tractor tyre for midrange tractors.
- Its special tread pattern with curved lugs provides good traction and self-cleaning.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life



## **Technical Informations**

| Item number                  | 14826380       |
|------------------------------|----------------|
|                              |                |
| EAN                          | 8714692336591  |
| Valid tyre size              | 380 / 85 R 30  |
| Alternative size 1           | 14.9R30        |
| LI / SI / PR                 | 135 A8 / 135 B |
| TL/TT                        | TL             |
| Brand                        | Vredestein     |
| Tread pattern                | TRAXION 85 II  |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 86,00          |
| Recommended rim size         | W12            |
| Permitted rim size           | W11, W13       |
| Maximum air pressure [bar].  | 1,60           |
| Section width (mm)           | 390            |
| Outer diameter of tyre [mm]. | 1410           |
| Stat. radius (SLR) [mm]      | 645            |
| Rolling circumference [mm].  | 4150           |
| Tread depth (mm)             | 43,0           |
| Tyre capacity 75% [ltr.]     | 230            |
| E-Ready                      | No             |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 135 A8 | 2180               | 40           |               | 1,60                        |              |
| 135 B  | 2180               | 50           |               | 1,60                        |              |