

TYRES

| Product group | Tyres |
|-----------------|----------------|
| Item number | 14826390 |
| Valid tyre size | 420 / 85 R 34 |
| LI / SI / PR | 142 A8 / 142 B |
| TL/TT | TL |
| Brand | Vredestein |
| Tread pattern | TRAXION 85 |





Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range tractors
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.



Technical Informations

| Item number | 14826390 |
|------------------------------|------------------|
| EAN | 8714692109836 |
| Valid tyre size | 420 / 85 R 34 |
| Alternative size 1 | 16.9R34 |
| LI / SI / PR | 142 A8 / 142 B |
| TL/TT | TL |
| Brand | Vredestein |
| Tread pattern | TRAXION 85 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 115,00 |
| Recommended rim size | DW15L |
| Permitted rim size | W14, DW14L, W15L |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 455 |
| Outer diameter of tyre [mm]. | 1570 |
| Stat. radius (SLR) [mm] | 735 |
| Rolling circumference [mm]. | 4700 |
| Tread depth (mm) | 45,4 |
| Tyre capacity 75% [ltr.] | 265 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 142 A8 | 2650 | 40 | | 1,60 | |
| 142 B | 2650 | 50 | | 1,60 | |