

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 14826395 |
| Valid tyre size | 460 / 85 R 34 |
| LI / SI / PR | 147 A8 / 147 B |
| TL/TT | TL |
| Brand | Vredestein |
| Tread pattern | TRAXION 85 |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.

Technical Informations

| | |
|------------------------------|--------------------------------|
| Item number | 14826395 |
| EAN | 8714692109843 |
| Valid tyre size | 460 / 85 R 34 |
| Alternative size 1 | 18.4R34 |
| LI / SI / PR | 147 A8 / 147 B |
| TL/TT | TL |
| Brand | Vredestein |
| Tread pattern | TRAXION 85 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 137,72 |
| Recommended rim size | DW16L |
| Permitted rim size | W14L, DW14L, W15L, DW15L, W16L |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 490 |
| Outer diameter of tyre [mm]. | 1640 |
| Stat. radius (SLR) [mm] | 765 |
| Rolling circumference [mm]. | 4915 |
| Tread depth (mm) | 48,0 |
| Tyre capacity 75% [ltr.] | 340 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 147 A8 | 3075 | 40 | | 1,60 | |
| 147 B | 3075 | 50 | | 1,60 | |