

TYRES

Product group	Tyres
Item number	14827110
Valid tyre size	VF 650 / 60 R 34 NRO
LI / SI / PR	168 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION OPTIMALL



Notes and features

- The Vredestein Traxion Optimall is an innovative VF tyre for high-performance tractors.
- Its extremely flexible casing design enables a reduction of the inflation pressure by up to 25% for low soil compaction.
- The upper bead zone is specially reinforced and provides good stability, even at low inflation pressure.
- The strong lug end in the tread centre provides stability, low wear and good self-cleaning properties.
- In on-road use, the tread with a high rubber content ensures slow wear and a long service life.
- The rounded tread contour enables good ride comfort.

Technical Informations

Item number	14827110
EAN	8714692344848
Valid tyre size	VF 650 / 60 R 34 NRO
LI / SI / PR	168 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION OPTIMALL
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	236,00
Recommended rim size	DW23B
Permitted rim size	DW21B
Maximum air pressure [bar].	2,00
Section width (mm)	650
Outer diameter of tyre [mm].	1660
Stat. radius (SLR) [mm]	750
Rolling circumference [mm].	4935
Tread depth (mm)	53,0
Tyre capacity 75% [ltr.]	457
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		2,00	