

## TYRES

Product group	Tyres
Item number	14827145
Valid tyre size	VF 900 / 60 R 42 NRO
LI / SI / PR	189 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION OPTIMALL



## Notes and features

- The Vredestein Traxion Optimall is an innovative VF tyre for high-performance tractors.
- Its extremely flexible casing design enables a reduction of the inflation pressure by up to 25% for low soil compaction.
- The upper bead zone is specially reinforced and provides good stability, even at low inflation pressure.
- The strong lug end in the tread centre provides stability, low wear and good self-cleaning properties.
- In on-road use, the tread with a high rubber content ensures slow wear and a long service life.
- The rounded tread contour enables good ride comfort.

## Technical Informations

Item number	14827145
EAN	8714692350771
Valid tyre size	VF 900 / 60 R 42 NRO
LI / SI / PR	189 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION OPTIMALL
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	458,26
Recommended rim size	DW30B
Permitted rim size	DW28B
Maximum air pressure [bar].	2,00
Section width (mm)	900
Outer diameter of tyre [mm].	2145
Stat. radius (SLR) [mm]	920
Rolling circumference [mm].	6315
Tread depth (mm)	64,0
Tyre capacity 75% [ltr.]	1112
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
189 D	10300	65		2,00	