

## TYRES

Product group	Tyres
Item number	14827148
Valid tyre size	VF 800 / 70 R 42
LI / SI / PR	189 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION OPTIMALL



## Notes and features

- The Vredestein Traxion Optimall is an innovative VF tyre for high-performance tractors.
- Its extremely flexible casing design enables a reduction of the inflation pressure by up to 25% for low soil compaction.
- The upper bead zone is specially reinforced and provides good stability, even at low inflation pressure.
- The strong lug end in the tread centre provides stability, low wear and good self-cleaning properties.
- In on-road use, the tread with a high rubber content ensures slow wear and a long service life.
- The rounded tread contour enables good ride comfort.

**Technical Informations**

<b>Item number</b>	14827148
<b>EAN</b>	8714692350757
<b>Valid tyre size</b>	VF 800 / 70 R 42
<b>LI / SI / PR</b>	189 D
<b>TL/TT</b>	TL
<b>Brand</b>	Vredestein
<b>Tread pattern</b>	TRAXION OPTIMALL
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	ECE 106
<b>Nettogewicht [kg] (gültig)</b>	439,63
<b>Recommended rim size</b>	DW27B
<b>Permitted rim size</b>	DW25B
<b>Maximum air pressure [bar].</b>	2,00
<b>Section width (mm)</b>	800
<b>Outer diameter of tyre [mm].</b>	2165
<b>Stat. radius (SLR) [mm]</b>	930
<b>Rolling circumference [mm].</b>	6380
<b>Tread depth (mm)</b>	64,0
<b>Tyre capacity 75% [ltr.]</b>	1043
<b>E-Ready</b>	No

**Load capacity**

<b>Index</b>	<b>Load capacity [kg]</b>	<b>Speed [km/h]</b>	<b>Axle position</b>	<b>Inflation pressure [bar]</b>	<b>Load variant</b>
189 D	10300	65		2,00	