

TYRES

Product group	Tyres	
Item number	14875050	
Valid tyre size	460 / 70 R 24	
LI / SI / PR	159 A8 / 159 B	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	TRAXION VERSA	





Notes and features

- The Vredestein Traxion Versa is an agro-industrial tyre for telescopic handlers, backhoe loaders and combine harvesters.
- Due to the shape and arrangement of its lugs, the tyre offers a flat and large contact area.
- The curved lugs are wider in the tread centre and thus enable good traction.
- Its reinforced sidewall in combination with a stabiliser ring guarantees maximum protection against tyre damages.



Technical Informations

Item number	14875050
EAN	8714692309946
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION VERSA
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	109,00
Recommended rim size	DW15L
Permitted rim size	DW14L, DW16L
Maximum air pressure [bar].	4,00
Section width (mm)	480
Outer diameter of tyre [mm].	1255
Stat. radius (SLR) [mm]	570
Rolling circumference [mm].	3800
Tread depth (mm)	38,0
Tyre capacity 75% [ltr.]	215
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
159 B	4375	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.