

TYRES

Product group	Tyres
Item number	14875340
Valid tyre size	400 / 80 R 24
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	Vredestein
Tread pattern	ENDURION



Notes and features

- The Vredestein Endurion is an MPT radial tyre for telescopic loaders and similar vehicles.
- Wide lugs arranged at a 45° angle to each other and the high tread pattern percentage ensure a long service life.
- The optimum rubber compound and the particularly sturdy casing increase the service life and guarantee maximum yields.

Technical Informations

Item number	14875340
EAN	8714692335419
Valid tyre size	400 / 80 R 24
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	Vredestein
Tread pattern	ENDURION
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	96,00
Recommended rim size	DW13
Permitted rim size	13
Maximum air pressure [bar].	5,00
Section width (mm)	410
Outer diameter of tyre [mm].	1245
Stat. radius (SLR) [mm]	570
Rolling circumference [mm].	3720
Tread depth (mm)	30,0
Tyre capacity 75% [ltr.]	158
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		5,00	
162 B	4750	50		5,00	