Bohnenkamp Moving Professionals

TYRES

| Product group | Tyres | |
|-----------------|----------------|--|
| ltere erreber | 14075250 | |
| Item number | 14875350 | |
| Valid tyre size | 480 / 80 R 26 | |
| LI / SI / PR | 160 A8 / 160 B | |
| TL/TT | TL | |
| Brand | Vredestein | |
| Tread pattern | ENDURION | |



Notes and features

- The Vredestein Endurion is an MPT radial tyre for telescopic loaders and similar vehicles.
- Wide lugs arranged at a 45° angle to each other and the high tread pattern percentage ensure a long service life.
- The optimum rubber compound and the particularly sturdy casing increase the service life and guarantee maximum yields.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 14875350 |
|------------------------------|----------------|
| EAN | 8714692310041 |
| Valid tyre size | 480 / 80 R 26 |
| LI / SI / PR | 160 A8 / 160 B |
| TL/TT | ть |
| Brand | Vredestein |
| Tread pattern | ENDURION |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |
| Nettogewicht [kg] (gültig) | 128,00 |
| Recommended rim size | DW15L |
| Permitted rim size | DW16L |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 495 |
| Outer diameter of tyre [mm]. | 1440 |
| Stat. radius (SLR) [mm] | 645 |
| Rolling circumference [mm]. | 4320 |
| Tread depth (mm) | 30,0 |
| Tyre capacity 75% [ltr.] | 283 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 160 A8 | 4500 | 40 | | 3,20 | |
| 160 B | 4500 | 50 | | 3,20 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.