

TYRES

Product group	Tyres
Item number	15211600
Valid tyre size	6.5 / 80 - 15
LI / SI / PR	98 A6 / 94 A8, 6 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

Item number	15211600
EAN	8903635001508
Valid tyre size	6.5 / 80 - 15
LI / SI / PR	98 A6 / 94 A8, 6 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	10,89
Recommended rim size	5.00F
Maximum air pressure [bar].	3,60
Section width (mm)	163
Outer diameter of tyre [mm].	663
Stat. radius (SLR) [mm]	295
Rolling circumference [mm].	1942
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
98 A6	750	30		3,60	
94 A8	670	40		3,60	