Bohnenkamp Moving Professionals

22.09.2024

TYRES

Product group	Tyres	
Item number	15211616	
Valid tyre size	10.0 / 75 - 15.3	
LI / SI / PR	136 A6 / 132 A8, 14 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	320 Value Plus	





Notes and features

- The Alliance 320 Value Plus is a tyre for agricultural trailers.
- The tyre's large contact area is gentle on the soil and enables applications on delicate grass surfaces and soils.
- Its strong nylon construction guarantees a long service life and optimum performance in the field and on the road.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number5211616EAN80363012997Vald tyre size10.0/75-15.3L/SI / PR36.66/132.48.14 PRTLTTT.PandNaJanoe20.Value PlusAntistaicNoTyre colourBlackECE regulation numberECE 106Nationamient regulation9.0Antionamient regulation9.0		
Valid tyre sizei0.0/75-15.3LI / SI / PR36.66 / 132.A8, 14 PRTLTTILBrandAlianceAliance20.Value PlusAntistaticNoTyre colourBlackECE regulation numberECE 106Nettogewicht [kg] (gültig)1,98Antistani Pressure [ka].50.Section vidth (mm)264Guer diameter of tyre [ka]363Andiace for signal (section for signal (secti	Item number	15211616
Li / Si / PRLi / Si / A6 / 132 A8, 14 PRTLTTT.TandNaPrandAlliance20 Value PlusAnistaticNoTyre colourBlackECE regulation numberECE 106Notogewich [kg] (gültig)1.9.9Antoman ir pressure [back.0.0Section width (mm).0.9Section width (mm).0.9Section sigtes [back.0.0Section width (mm).0.9Section width (mm).0.9Section sigtes [back.0.0Section width (mm).0.9Section width (mm).0.9Section sigtes [back.0.0Section width (mm).0.9Section width (mm).0.9 <tr< th=""><th>EAN</th><th>8903635012597</th></tr<>	EAN	8903635012597
TLTTITLTTIBrandAlianceTread pattern30 Value PlusAntistaticNoFyre colourBiackECE regulation numberCE 106Retongewich [kg] (gild)1,93Antistatic9.0Becommended rim size9.0Section vidth (mm)1.6Section vidth (mm)1.6Biand Static (SLR) [mm]2.6Biand Static (SLR) [mm]2.6Static adius (SLR) [mm]2.3Biang circumference [mm]2.4Subant (SLR) [mm	Valid tyre size	10.0 / 75 - 15.3
BrandAlianceBrandAlianceTread pattern20 Value PlusAntistaticNoTyre colourBackBcachSci 106Fetregulation number4.98Notogewicht [kg] (gült)g)14.98Natumani pressure [bach7.50Section width (mm)16.04Back3.04	LI / SI / PR	136 A6 / 132 A8, 14 PR
Tread pattern320 Value PlusAntistaticNoTyre colourBlackECE regulation numberECE 106Nettogewicht [kg] (güttg)14,98Aecommended rim size9.00Maximum air pressure [baz]7.50Section width (mm)60Guter diameter of tyre [mm]60Rating (SLR) [mm]243Rolling circumference [mm]219Outer diameter of tyre [mm]200Stat. radius (SLR) [mm]243Subscience [mm]200Subscience [mm]200Subsci [mm]200Subsci [mm]<	TL/TT	TL
AntistaticNoTyre colourBlackECE regulation numberECE 106Nettogewicht [kg] (gültig)14,98Recommended rim size9.00Maxinum air pressure [bar]7.50Section width (mm)264Outer diameter of tyre [mm]343Rating (SLR) [mm]243Reling circumference [mm]7.90	Brand	Alliance
Tyre colourBlackECE regulation numberECE 106Nettogewicht [kg] (gültig)14,98Recommended rim size9.00Maxinum air pressure [baa]7.50Section width (mm)264Outer diameter of tyre [mm]343Rolling circumference [mm]2243Guarantee period7 years	Tread pattern	320 Value Plus
ECE regulation numberECE 106Nettogewicht [kg] (gütt)g14,98Recommended rim size9.00Maximum air pressure [bar]7.50Section width (mm)264Outer diameter of tyre [mm]700Stat. radius (SLR) [mm]243Rolling circumfence [mm]7.90Outer diameter of tyre [mm]7.90Stat. radius (SLR) [mm]2.91Outer diameter of tyre [mm]7.90Stat. radius (SLR) [mm]2.91Stat. radius (SLR) [mm]7.91Stat. radius (SLR) [mm]	Antistatic	No
Nettogewicht [kg] (üiltig)i.4,98Recommended rim size9.00Maximum air pressure [ba]7.50Section width (mm)264Outer diameter of tyre [mm]i.4.3Stat. radius (SLR) [mm]3.43Rolling circumference [mm]2.43Guarantee period7.9ars	Tyre colour	Black
Recommended rim size9.00Maximum air pressure [ba]7.50Section width (mm)64Outer diameter of tyre [mm]7.00Stat. radius (SLR) [mm]3.43Rolling circumference [mm]7.92Yung Yang Yang Yang Yang Yang Yang Yang Ya	ECE regulation number	ECE 106
Maximum air pressure [bar] 7,50 Section width (mm) 264 Outer diameter of tyre [mm] 760 Stat. radius (SLR) [mm] 343 Rolling circumference [mm] 2243 Guarantee period 7 years	Nettogewicht [kg] (gültig)	14,98
Section width (mm)264Outer diameter of tyre [mm]760Stat. radius (SLR) [mm]343Rolling circumference [mm]2243Guarantee period7 years	Recommended rim size	9.00
Outer diameter of tyre [mm] 760 Stat. radius (SLR) [mm] 343 Rolling circumference [mm] 2433 Guarantee period 7 years	Maximum air pressure [bar].	7,50
Stat. radius (SLR) [mm] 343 Rolling circumference [m] 243 Guarantee period 7 years	Section width (mm)	264
Rolling circumference [mm] 2243 Guarantee period 7 years	Outer diameter of tyre [mm].	760
Guarantee period 7 years	Stat. radius (SLR) [mm]	343
	Rolling circumference [mm].	2243
E Deady	Guarantee period	7 years
E-Ready NO	E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 A6	2240	30	Free Rolling	7,50	LLV
132 A8	2000	40		7,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.