Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15211621	
Valid tyre size	10.0 / 75 - 15.3	
LI / SI / PR	122 A8 / 135 A8, 18 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	320	



Notes and features

Implement tyre with high load capacity. •

Strong nylon casing for a long service life. •

Low soil compaction.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number 15211621	
EAN 8903635008798	
Valid tyre size 10.0 / 75 - 15.3	
LI/SI/PR 122 A8 / 135 A8, 18 PR	
TL/TT TL	
Brand Alliance	
Tread pattern 320	
Antistatic No	
Tyre colour Black	
ECE regulation number ECE 106	
Nettogewicht [kg] (gültig) 20,58	
Recommended rim size 9.00	
Maximum air pressure [bar]. 7,10	
Section width (mm) 264	
Outer diameter of tyre [mm]. 760	
Stat. radius (SLR) [mm] 343	
Rolling circumference [mm]. 2243	
Tread depth (mm) 9,0	
Guarantee period 7 years	
E-Ready No	

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A8	1500	40	Drive Wheel	4,70	LLV
135 A8	2180	40	Free Rolling	4,70	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.