Bohnenkamp Moving Professionals

13.11.2024

TYRES

Product group	Tyres	
Item number	15211654	
Valid tyre size	400 / 60 - 15.5	
LI / SI / PR	132 A8 / 145 A8, 14 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotation 328	





Notes and features

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.

• Also for tractors (turf rolls).

Bohnenkamp Moving Professionals

Technical Informations

Item number	15211654
EAN	8903635000853
Valid tyre size	400 / 60 - 15.5
LI / SI / PR	132 A8 / 145 A8, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	33,40
Recommended rim size	13.00
Maximum air pressure [bar].	3,60
Section width (mm)	404
Outer diameter of tyre [mm].	874
Stat. radius (SLR) [mm]	377
Rolling circumference [mm].	2510
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 A8	2000	40	Drive Wheel	3,60	LLV
145 A8	2900	40	Free Rolling	3,60	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.