

TYRES

Product group	Tyres	
Item number	15211657	
Valid tyre size	500 / 60 - 15.5	
LI / SI / PR	157 A2 / 150 A8, 12 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestry 328	





Notes and features

- The Alliance Forestry 328 is a modern forestry tyre for lumber trailers, wood chippers and other towed forestry trailers.
- Due to the strong, steel-reinforced nylon casing, high undertread gauge, reinforced sidewalls and sturdy rubber compound, the tyre is very tough and durable.
- Its tread pattern has been specially adapted for forestry use.



Technical Informations

Item number	15211657
EAN	7291050002028
Valid tyre size	500 / 60 - 15.5
LI / SI / PR	157 A2 / 150 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 328
TRA Code	13
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	69,81
Recommended rim size	16.00
Maximum air pressure [bar].	3,30
Section width (mm)	503
Outer diameter of tyre [mm].	994
Stat. radius (SLR) [mm]	439
Rolling circumference [mm].	2894
Tyre capacity 75% [ltr.]	167.25
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A2	4125	10		3,30	
150 A8	3350	40		3,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.