

TYRES

Product group	Tyres	
Item number	15211683	
Valid tyre size	380 / 55 - 17	
LI / SI / PR	125 A8 / 138 A8, 12 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	FarmPRO 327	





Notes and features

- Modern implement tyre for trailers and other farm machines with various uses, on grassland in particular.
- Plant- and soil-protecting tread pattern.

- Large contact area for low ground pressure and machine stability (on implements).
- Non-directional tread pattern with low rolling resistance and good self-cleaning properties.



Technical Informations

Item number	15211683
EAN	8903635010425
Valid tyre size	380 / 55 - 17
Alternative size 1	15.0/55-17
LI / SI / PR	125 A8 / 138 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO 327
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	32,33
Recommended rim size	13
Maximum air pressure [bar].	2,80
Section width (mm)	391
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	384
Rolling circumference [mm].	2516
Tread depth (mm)	12,5
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A8	1650	40	Drive Wheel	2,80	
138 A8	2360	40	Free Rolling	2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.