

## **TYRES**

Product group	Tyres	
Item number	15211685	
Valid tyre size	500 / 50 - 17	
LI / SI / PR	143 A8 / 139 B, 10 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	320	



## Notes and features

- Implement tyre with high load capacity.
- Low soil compaction.

• Strong nylon casing for a long service life.



## **Technical Informations**

Item number	15211685
EAN	8903635014430
Valid tyre size	500 / 50 - 17
LI / SI / PR	143 A8 / 139 B, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	320
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	51,52
Recommended rim size	16
Maximum air pressure [bar].	2,70
Section width (mm)	500
Outer diameter of tyre [mm].	940
Stat. radius (SLR) [mm]	415
Rolling circumference [mm].	2736
Tread depth (mm)	13,0
Guarantee period	7 years
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	40		2,00	
139 B	2430	50		2,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.