

TYRES

Product group	Tyres	
Item number	15211695	
Valid tyre size	500 / 50 - 17	
LI / SI / PR	141 A8 / 154 A8, 18 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	FarmPRO 327	





Notes and features

- Modern implement tyre for trailers and other farm machines with various uses, on grassland in particular.
- Plant- and soil-protecting tread pattern.

- Large contact area for low ground pressure and machine stability (on implements).
- Non-directional tread pattern with low rolling resistance and good self-cleaning properties.



Technical Informations

Item number	15211695
EAN	8903635006459
Valid tyre size	500 / 50 - 17
LI / SI / PR	141 A8 / 154 A8, 18 PR
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO 327
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	56,90
Recommended rim size	16
Maximum air pressure [bar].	3,50
Section width (mm)	500
Outer diameter of tyre [mm].	960
Stat. radius (SLR) [mm]	435
Rolling circumference [mm].	2840
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A8	2575	40	Drive Wheel	3,50	
154	3750	40	Free Rolling	3,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.