

TYRES

Product group	Tyres	
Item number	15212315	
Valid tyre size	12.0 / 75 - 18	
LI / SI / PR	139 A6 / 135 A8, 12 PR	
TL/TT	тт	
Brand	Alliance	
Tread pattern	317 (Spacer)	





Notes and features

- Bias multi-purpose tyre for the most varied fields of application on a wide range of machines.
- Special tread pattern with angular blocks in the tread centre with bigger distance (spacers) between the lugs.
- Traction tread pattern for good traction and self-cleaning, even in difficult operation and weather conditions.
- Centrally-located tread bars for good vehicle handling on roads
- For longer, free-rolling use, mounting against the rolling direction is recommended.



Technical Informations

Item number	15212315
EAN	8903635007401
Valid tyre size	12.0 / 75 - 18
LI / SI / PR	139 A6 / 135 A8, 12 PR
TL/TT	тт
Brand	Alliance
Tread pattern	317 (Spacer)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	34,50
Recommended rim size	9
Maximum air pressure [bar].	4,00
Section width (mm)	299
Outer diameter of tyre [mm].	915
Stat. radius (SLR) [mm]	411
Rolling circumference [mm].	2690
Tread depth (mm)	18,0
Tyre capacity 75% [ltr.]	127
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A6	2430	30		4,00	
135 A8	2180	40		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.