

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 15212317 |
| Valid tyre size | 320 / 80 - 18 |
| LI / SI / PR | 129 A8 / 142 A8, 12 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | FarmPRO 327 |



Notes and features

- Modern implement tyre for trailers and other farm machines with various uses, on grassland in particular.
- Plant- and soil-protecting tread pattern.
- Large contact area for low ground pressure and machine stability (on implements).
- Non-directional tread pattern with low rolling resistance and good self-cleaning properties.

Technical Informations

| | |
|------------------------------|------------------------|
| Item number | 15212317 |
| EAN | 8903635010067 |
| Valid tyre size | 320 / 80 - 18 |
| Alternative size 1 | 12.5/80-18 |
| LI / SI / PR | 129 A8 / 142 A8, 12 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | FarmPRO 327 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 32,52 |
| Recommended rim size | 10 |
| Maximum air pressure [bar]. | 3,70 |
| Section width (mm) | 320 |
| Outer diameter of tyre [mm]. | 970 |
| Stat. radius (SLR) [mm] | 434 |
| Rolling circumference [mm]. | 2860 |
| Tread depth (mm) | 12,5 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 129 A8 | 1850 | 40 | Drive Wheel | 3,70 | |
| 142 A8 | 2650 | 40 | Free Rolling | 3,70 | |