

TYRES

Product group	Tyres	
Item number	15212400	
Valid tyre size	15.0 / 70 - 18	
LI / SI / PR	145 A8 / 141 B, 12 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	320	



Notes and features

- Implement tyre with high load capacity.
- Low soil compaction.

• Strong nylon casing for a long service life.



Technical Informations

Item number	15212400
EAN	8903635001485
Valid tyre size	15.0 / 70 - 18
LI / SI / PR	145 A8 / 141 B, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	320
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	41,63
Recommended rim size	13
Maximum air pressure [bar].	3,10
Section width (mm)	391
Outer diameter of tyre [mm].	990
Stat. radius (SLR) [mm]	442
Rolling circumference [mm].	2902
Tread depth (mm)	12,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		3,10	
141 B	2575	50		3,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.