

## **TYRES**

Bur doort amount	T	
Product group	Tyres	
Item number	15212405	
Valid tyre size	15.0 / 70 - 18	
LI / SI / PR	151 A8 / 147 B, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	320	



## Notes and features

- Implement tyre with high load capacity.
- Low soil compaction.

• Strong nylon casing for a long service life.



## **Technical Informations**

Item number	15212405
EAN	8903635001904
Valid tyre size	15.0 / 70 - 18
LI / SI / PR	151 A8 / 147 B, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	320
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	45,08
Recommended rim size	13
Maximum air pressure [bar].	4,25
Section width (mm)	391
Outer diameter of tyre [mm].	990
Stat. radius (SLR) [mm]	442
Rolling circumference [mm].	2902
Tread depth (mm)	12,0
Guarantee period	7 years
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		4,21	LLV
147 B	3075	50		4,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.