Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres	
Item number	15212480	
Valid tyre size	16.0 / 70 - 20	
LI / SI / PR	151 A8 / 147 B, 12 PR	
TL/TT	тт	
Brand	Alliance	
Tread pattern	320	



Notes and features

- Implement tyre with high load capacity.
- Low soil compaction.

• Strong nylon casing for a long service life.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15212480
EAN	8903635002499
Valid tyre size	16.0 / 70 - 20
LI / SI / PR	151 A8 / 147 B, 12 PR
TL/TT	ТТ
Brand	Alliance
Tread pattern	320
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	47,89
Recommended rim size	13.00
Permitted rim size	12
Maximum air pressure [bar].	3,00
Section width (mm)	418
Outer diameter of tyre [mm].	1075
Stat. radius (SLR) [mm]	465
Rolling circumference [mm].	3140
Tread depth (mm)	13,5
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,00	
147 B	3075	50		3,00	

05.02.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.