

TYRES

| | |
|-----------------|-----------------------|
| Product group | Tyres |
| Item number | 15212485 |
| Valid tyre size | 16.0 / 70 - 20 |
| LI / SI / PR | 154 A8 / 150 B, 14 PR |
| TL/TT | TT |
| Brand | Alliance |
| Tread pattern | 320 |



Notes and features

- Implement tyre with high load capacity.
- Low soil compaction.
- Strong nylon casing for a long service life.

Technical Informations

| | |
|------------------------------|-----------------------|
| Item number | 15212485 |
| EAN | 8903635002505 |
| Valid tyre size | 16.0 / 70 - 20 |
| LI / SI / PR | 154 A8 / 150 B, 14 PR |
| TL/TT | TT |
| Brand | Alliance |
| Tread pattern | 320 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 50,58 |
| Recommended rim size | 13.00 |
| Permitted rim size | 12 |
| Maximum air pressure [bar]. | 3,50 |
| Section width (mm) | 418 |
| Outer diameter of tyre [mm]. | 1075 |
| Stat. radius (SLR) [mm] | 470 |
| Rolling circumference [mm]. | 3164 |
| Tread depth (mm) | 13,5 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 154 A8 | 3750 | 40 | | 3,50 | |
| 150 B | 3350 | 50 | | 3,50 | |