

## **TYRES**

Product group	Tyres	
Item number	15212488	
Valid tyre size	400 / 70 - 20	
LI / SI / PR	139 A8 / 151 A8, 12 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	FarmPRO 327	





## Notes and features

- Modern implement tyre for trailers and other farm machines with various uses, on grassland in particular.
- Plant- and soil-protecting tread pattern.

- Large contact area for low ground pressure and machine stability (on implements).
- Non-directional tread pattern with low rolling resistance and good self-cleaning properties.



## **Technical Informations**

Item number	15212488
EAN	8903635009351
Valid tyre size	400 / 70 - 20
Alternative size 1	16.0/70-20
LI / SI / PR	139 A8 / 151 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO 327
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	48,70
Recommended rim size	13
Maximum air pressure [bar].	3,00
Section width (mm)	408
Outer diameter of tyre [mm].	1075
Stat. radius (SLR) [mm]	476
Rolling circumference [mm].	3112
Tread depth (mm)	14,0
Guarantee period	7 years
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A8	2430	40	Drive Wheel	3,00	
151 A8	3450	40	Free Rolling	3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.