

TYRES

| | |
|-----------------|-----------------------|
| Product group | Tyres |
| Item number | 15212550 |
| Valid tyre size | 20.00 - 20 |
| LI / SI / PR | 169 A8 / 165 B, 20 PR |
| TL/TT | TT |
| Brand | Alliance |
| Tread pattern | 222 |



Notes and features

- The Alliance 222 is an implement tyre for agricultural trailers and towed machines.
- The high-volume tyre with extra wide contact area offers high loading capacity and optimum soil protection at the same time.
- It is ideally suitable for field applications and road transport.

Technical Informations

| | |
|------------------------------|-----------------------|
| Item number | 15212550 |
| EAN | 7291050000062 |
| Valid tyre size | 20.00 - 20 |
| LI / SI / PR | 169 A8 / 165 B, 20 PR |
| TL/TT | TT |
| Brand | Alliance |
| Tread pattern | 222 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 88,23 |
| Recommended rim size | 16 |
| Permitted rim size | 20SDC |
| Maximum air pressure [bar]. | 3,90 |
| Section width (mm) | 498 |
| Outer diameter of tyre [mm]. | 1400 |
| Stat. radius (SLR) [mm] | 598 |
| Rolling circumference [mm]. | 3991 |
| Tread depth (mm) | 12,0 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 169 A8 | 5800 | 30 | Free Rolling | 3,90 | |
| 165 B | 5150 | 40 | Free Rolling | 3,90 | |