

TYRES

Product group	Tyres
Item number	15212558
Valid tyre size	21.0 / 80 - 20
LI / SI / PR	154 A8 / 166 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	222



Notes and features

- The Alliance 222 is an implement tyre for agricultural trailers and towed machines.
- The high-volume tyre with extra wide contact area offers high loading capacity and optimum soil protection at the same time.
- It is ideally suitable for field applications and road transport.

Technical Informations

Item number	15212558
EAN	8903635027850
Valid tyre size	21.0 / 80 - 20
LI / SI / PR	154 A8 / 166 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	222
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	84,00
Recommended rim size	16
Maximum air pressure [bar].	2,20
Section width (mm)	525
Outer diameter of tyre [mm].	1384
Stat. radius (SLR) [mm]	573
Rolling circumference [mm].	4080
Tread depth (mm)	12,2
Tyre capacity 75% [ltr.]	316.31
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40	Free Rolling	2,20	
166	5300	40	Drive Wheel	2,20	