

TYRES

Product group	Tyres	
Item number	15212565	
Valid tyre size	500 / 45 - 20	
LI / SI / PR	164 A6 / 160 A8, 18 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotation 331	





Notes and features

- The Alliance 331 HD is a tyre for excavators, developed to carry heavy loads under difficult conditions.
- The Alliance 331 HD replaces dual configurations for smaller wheeled excavators - range 7,000 to 25,000 kg.
- The tyre provides significant stability, high ride comfort and good machine manoeuvrability.
- It also provides good self-cleaning properties, high traction and excellent overall performance on the road.
- Due to its special heavy-duty construction and bead reinforcement, the tyre is very robust and durable.



Technical Informations

Item number	15212565
EAN	7291050012553
Valid tyre size	500 / 45 - 20
LI / SI / PR	164 A6 / 160 A8, 18 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 331
Carcass properties	HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	64,38
Recommended rim size	16.00DC
Permitted rim size	W16
Maximum air pressure [bar].	6,00
Section width (mm)	490
Outer diameter of tyre [mm].	980
Stat. radius (SLR) [mm]	442
Speed Radius Index (SRI)	475
Rolling circumference [mm].	3050
Contact area [cm²]	971.0
Tread depth (mm)	20,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	126.00
Guarantee period	5 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A6	5000	30		6,00	
160 A8	4500	40		6,00	