

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 15212568 |
| Valid tyre size | 500 / 55 - 20 |
| LI / SI / PR | 138 A8 / 150 A8, 10 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | FarmPRO 327 |



Notes and features

- Modern implement tyre for trailers and other farm machines with various uses, on grassland in particular.
- Plant- and soil-protecting tread pattern.
- Large contact area for low ground pressure and machine stability (on implements).
- Non-directional tread pattern with low rolling resistance and good self-cleaning properties.

Technical Informations

| | |
|------------------------------|------------------------|
| Item number | 15212568 |
| EAN | 8903635004189 |
| Valid tyre size | 500 / 55 - 20 |
| LI / SI / PR | 138 A8 / 150 A8, 10 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | FarmPRO 327 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 56,06 |
| Recommended rim size | 16.00 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 503 |
| Outer diameter of tyre [mm]. | 1055 |
| Stat. radius (SLR) [mm] | 464 |
| Rolling circumference [mm]. | 3063 |
| Tread depth (mm) | 12,6 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 138 A8 | 2360 | 40 | Drive Wheel | 2,40 | |
| 150 A8 | 3350 | 40 | Free Rolling | 2,40 | |