

TYRES

Product group	Tyres
Item number	15212575
Valid tyre size	500 / 45 - 22.5
LI / SI / PR	142 A8 / 154 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328



Notes and features

- Bias flotation tyre for towed vehicles.
- Also for tractors (turf rolls).
- Soil-protecting tread pattern.

Technical Informations

Item number	15212575
EAN	8903635002598
Valid tyre size	500 / 45 - 22.5
LI / SI / PR	142 A8 / 154 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	73,39
Recommended rim size	16.00
Maximum air pressure [bar].	3,60
Section width (mm)	500
Outer diameter of tyre [mm].	1030
Stat. radius (SLR) [mm]	455
Rolling circumference [mm].	3153
Tread depth (mm)	25,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40	Drive Wheel	3,60	
154 A8	3750	40	Free Rolling	3,60	