

TYRES

Product group	Tyres	
Item number	15212575	
Valid tyre size	500 / 45 - 22.5	
LI / SI / PR	142 A8 / 154 A8, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotation 328	





Notes and features

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.

Also for tractors (turf rolls).



Technical Informations

Item number	15212575
EAN	8903635002598
Valid tyre size	500 / 45 - 22.5
LI / SI / PR	142 A8 / 154 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	73,39
Recommended rim size	16.00
Maximum air pressure [bar].	3,60
Section width (mm)	500
Outer diameter of tyre [mm].	1030
Stat. radius (SLR) [mm]	455
Rolling circumference [mm].	3153
Tread depth (mm)	25,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40	Drive Wheel	3,60	
154 A8	3750	40	Free Rolling	3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.