

TYRES

Product group	Tyres
Item number	15212584
Valid tyre size	500 / 60 - 22.5
LI / SI / PR	153 A8 / 165 A8, 18 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328



Notes and features

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.
- Also for tractors (turf rolls).

Technical Informations

Item number	15212584
EAN	8903635021155
Valid tyre size	500 / 60 - 22.5
LI / SI / PR	153 A8 / 165 A8, 18 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	81,00
Recommended rim size	16.00
Maximum air pressure [bar].	3,60
Section width (mm)	500
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	510
Rolling circumference [mm].	3470
Tread depth (mm)	26,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40	Drive Wheel	3,60	
165 A8	5150	40	Free Rolling	3,60	