

## TYRES

Product group	Tyres
Item number	15212585
Valid tyre size	500 / 60 - 22.5
LI / SI / PR	158 A2 / 151 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 331



## Notes and features

- The Alliance Forestry 331 forest was developed for use on modern harvesters and transport vehicles in the forestry sector.
- It is also highly-suitable for mobile excavators, wheel loaders and dumpers working on difficult terrain.
- The tyre can also be used in agriculture for cultivating tough and abrasive surfaces.
- The tyre is characterised by high traction, low slip and low fuel consumption.
- Its huge volume ensures low soil compaction and good ride comfort in forestry and agricultural applications.
- Due to its strong nylon casing with steel belts, high undertread gauge, reinforced sidewalls and a sturdy rubber compound, the tyre is extremely robust and durable.

## Technical Informations

Item number	15212585
EAN	7291050012997
Valid tyre size	500 / 60 - 22.5
LI / SI / PR	158 A2 / 151 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 331
TRA Code	I3
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	110,01
Recommended rim size	16.00
Maximum air pressure [bar].	3,20
Section width (mm)	500
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	540
Rolling circumference [mm].	3500
Tread depth (mm)	39,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A2	4250	10		3,20	
151 A8	3450	40		3,20	