

TYRES

Product group	Tyres
Item number	15212591
Valid tyre size	550 / 45 - 22.5
LI / SI / PR	147 A8 / 159 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	328 Value Plus



Notes and features

- Flotation tyre with traction pattern for light conditions, e.g. on towed and mounted equipment as well as agricultural trailers, presses etc.
- Very good self-cleaning properties and simultaneous soil protection due to traction tread pattern.
- Rounded shoulders additionally protect green areas and plant stock.
- Not suitable for heavy vehicles and/or long road journeys under high loads.

Technical Informations

Item number	15212591
EAN	8903635011378
Valid tyre size	550 / 45 - 22.5
LI / SI / PR	147 A8 / 159 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	328 Value Plus
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	73,20
Recommended rim size	16.00DC
Permitted rim size	18.00DC
Maximum air pressure [bar].	3,80
Section width (mm)	550
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	470
Rolling circumference [mm].	3105
Tread depth (mm)	26,0
Number of lugs	26x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40	Drive Wheel	3,80	
159 A8	4375	40	Free Rolling	3,80	