Bohnenkamp
Moving Professionals

TYRES

Product group	Tyres
Item number	15212598
Valid tyre size	550 / 45 - 22.5
LI / SI / PR	147 A8 / 159 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD

Notes and features

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.
- Also for tractors (turf rolls).

Technical Informations

Item number	15212598
EAN	8903635002611
Valid tyre size	550 / 45 - 22.5
LI / SI / PR	147 A8 / 159 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	76,28
Recommended rim size	16.00
Permitted rim size	18.00
Maximum air pressure [bar].	2,80
Section width (mm)	550
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	476
Rolling circumference [mm].	3175
Tread depth (mm)	25,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40	Drive Wheel	2,80	
159 A8	4375	40	Free Rolling	2,80	