

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 15212616 |
| Valid tyre size | 550 / 60 - 22.5 |
| LI / SI / PR | 154 A8 / 166 A8, 16 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Flotation 328 |



Notes and features

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.
- Also for tractors (turf rolls).

Technical Informations

| | |
|------------------------------|------------------------|
| Item number | 15212616 |
| EAN | 8903635003274 |
| Valid tyre size | 550 / 60 - 22.5 |
| LI / SI / PR | 154 A8 / 166 A8, 16 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Flotation 328 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 89,80 |
| Recommended rim size | 16.00 |
| Maximum air pressure [bar]. | 3,00 |
| Section width (mm) | 550 |
| Outer diameter of tyre [mm]. | 1238 |
| Stat. radius (SLR) [mm] | 540 |
| Speed Radius Index (SRI) | 600 |
| Rolling circumference [mm]. | 3765 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 154 A8 | 3750 | 40 | Drive Wheel | 3,00 | |
| 166 A8 | 5300 | 40 | Free Rolling | 3,00 | |