

## **TYRES**

Product group	Tyres	
Item number	15212625	
Valid tyre size	550 / 60 - 22.5	
LI / SI / PR	154 A8 / 166 A8, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	328 Value Plus	





## Notes and features

- Flotation tyre with traction pattern for light conditions, e.g. on towed and mounted equipment as well as agricultural trailers, presses etc.
- Very good self-cleaning properties and simultaneous soil protection due to traction tread pattern.
- Rounded shoulders additionally protect green areas and plant stock.
- Not suitable for heavy vehicles and/or long road journeys under high loads.



## **Technical Informations**

Item number	15212625
EAN	8903635011354
Valid tyre size	550 / 60 - 22.5
LI / SI / PR	154 A8 / 166 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	328 Value Plus
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	85,60
Recommended rim size	16.00DC
Maximum air pressure [bar].	3,00
Section width (mm)	550
Outer diameter of tyre [mm].	1238
Stat. radius (SLR) [mm]	540
Rolling circumference [mm].	3765
Tread depth (mm)	26,0
Number of lugs	30x2
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40	Drive Wheel	3,00	
166 A8	5300	40	Free Rolling	3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.