

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 15212632 |
| Valid tyre size | 600 / 50 - 22.5 |
| LI / SI / PR | 158 A2 / 151 A8, 16 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Forestar 344 |



Notes and features

- The Alliance Forestar 344 is a powerful forestry tyre for CTL machines.
- The steel-reinforced nylon casing, the special rubber compound, as well as the reinforced sidewalls, protect the tyre against punctures.
- The traction tread pattern with low-angled lugs provides excellent grip and good self-cleaning thanks to wide gaps between the lugs.
- Due to the close spacing of the lugs in the centre of the tread, the rolling resistance can be reduced on hard surfaces.
- Matching chains and ribbons are available on the market.

Technical Informations

| | |
|------------------------------|------------------------|
| Item number | 15212632 |
| EAN | 7291050042833 |
| Valid tyre size | 600 / 50 - 22.5 |
| LI / SI / PR | 158 A2 / 151 A8, 16 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Forestar 344 |
| TRA Code | LS-2 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 153,23 |
| Recommended rim size | 20.00 |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 600 |
| Outer diameter of tyre [mm]. | 1170 |
| Stat. radius (SLR) [mm] | 540 |
| Rolling circumference [mm]. | 3502 |
| Tread depth (mm) | 51,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 158 A2 | 4250 | 10 | | 3,20 | |
| 151 A8 | 3450 | 40 | | 3,20 | |