

## **TYRES**

Product group	Tyres	
Item number	15212638	
Valid tyre size	600 / 50 - 22.5	
LI / SI / PR	158 D / 157 E, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotation 328	





## **Notes and features**

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.

• Also for tractors (turf rolls).



## **Technical Informations**

Item number	15212638
EAN	7291050005296
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	158 D / 157 E, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	99,13
Recommended rim size	20.00
Maximum air pressure [bar].	2,60
Section width (mm)	600
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	520
Rolling circumference [mm].	3450
Tread depth (mm)	25,0
Guarantee period	7 years
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		2,60	
157 E	4125	70		2,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.