

TYRES

Product group	Tyres
Item number	15212639
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	153 A8 / 165 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 331



Notes and features

- The Alliance 331 is perfectly suited to on- and off-road agricultural applications e.g. for tractors, agricultural trailers and similar vehicles.
- Its main characteristics are a high load capacity and low inflation pressure.
- It replaces conventional tractor tyres or dual constructions because of its high traction, high load capacity and at the same time protects the soil.
- Thanks to the permitted speed of 50 km/h, it can also be used on off-road trucks and trailers.
- The strong nylon construction and special rubber compound make the tyre very durable.

Technical Informations

Item number	15212639
EAN	7291050041447
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	153 A8 / 165 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 331
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	102,53
Recommended rim size	20.00
Permitted rim size	AG20.00
Maximum air pressure [bar].	2,60
Section width (mm)	600
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	518
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3542
Contact area [cm ²]	1403
Tread depth (mm)	40,0
Number of lugs	19x2
Tyre capacity 75% [litr.]	250
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40	Drive Wheel	2,60	
165 A8	5150	40	Free Rolling	2,60	