

TYRES

Product group	Tyres
Item number	15212648
Valid tyre size	600 / 55 - 22.5
LI / SI / PR	162 D / 161 E, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328



Notes and features

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.
- Also for tractors (turf rolls).

Technical Informations

Item number	15212648
EAN	7291050005999
Valid tyre size	600 / 55 - 22.5
LI / SI / PR	162 D / 161 E, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	102,58
Recommended rim size	20.00
Maximum air pressure [bar].	2,80
Section width (mm)	600
Outer diameter of tyre [mm].	1270
Stat. radius (SLR) [mm]	550
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3650
Tread depth (mm)	30,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 D	4750	65		2,80	
161 E	4625	70		2,80	