

TYRES

Product group	Tyres	
Item number	15212662	
Valid tyre size	710 / 40 - 22.5	
LI / SI / PR	161 A2 / 154 A8, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestar 344	





Notes and features

- The Alliance Forestar 344 is a powerful forestry tyre for CTL machines.
- The steel-reinforced nylon casing, the special rubber compound, as well as the reinforced sidewalls, protect the tyre against punctures.
- The traction tread pattern with low-angled lugs provides excellent grip and good self-cleaning thanks to wide gaps between the lugs.
- Due to the close spacing of the lugs in the centre of the tread, the rolling resistance can be reduced on hard surfaces.
- Matching chains and ribbons are available on the market.



Technical Informations

Item number	15212662
EAN	7291050042840
Valid tyre size	710 / 40 - 22.5
LI / SI / PR	161 A2 / 154 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	163,08
Recommended rim size	24.00
Maximum air pressure [bar].	3,60
Section width (mm)	700
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	540
Rolling circumference [mm].	3502
Tread depth (mm)	51,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 A2	4625	10		3,60	
154 A8	3750	40		3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.