Bohnenkamp Moving Professionals

21.09.2024

TYRES

Product group	Tyres	
Item number	15212670	
Valid tyre size	700 / 50 - 22.5	
LI / SI / PR	167 D / 166 E, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotation 328	





Notes and features

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.

• Also for tractors (turf rolls).

Bohnenkamp Moving Professionals

Technical Informations

Item number	15212670
EAN	7291050039505
Valid tyre size	700 / 50 - 22.5
LI / SI / PR	167 D / 166 E, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	121,31
Recommended rim size	24.00
Maximum air pressure [bar].	2,80
Section width (mm)	700
Outer diameter of tyre [mm].	1270
Stat. radius (SLR) [mm]	550
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3650
Tread depth (mm)	25,0
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 D	5450	65		2,80	
166 E	5300	70		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.