

TYRES

Product group	Tyres
Item number	15212674
Valid tyre size	800 / 35 - 22.5
LI / SI / PR	169 A8 / 162 D, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	128



Notes and features

- The Alliance 128 was designed for agricultural trailers in the field and on the road.
- The special tread pattern with shoulder lugs provides high traction in the field.
- The grooved tread pattern in the middle of the tread provides comfortable driving performance on roads during transport journeys.
- The tyre enables high loading capacity at low inflation pressure, optimum soil protection and low rolling resistance.
- Its strong nylon casing and rubber compound guarantee a long service life.

Technical Informations

Item number	15212674
EAN	7291050082136
Valid tyre size	800 / 35 - 22.5
LI / SI / PR	169 A8 / 162 D, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	128
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	132,68
Recommended rim size	28.00
Permitted rim size	24.00, 26.00
Maximum air pressure [bar].	2,60
Section width (mm)	800
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	523
Rolling circumference [mm].	3508
Tread depth (mm)	26,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	325
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A8	5800	40		2,60	
162 D	4750	65		2,60	