

TYRES

Product group	Tyres	
Item number	15212674	
Valid tyre size	800 / 35 - 22.5	
LI / SI / PR	169 A8 / 162 D, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	128	





Notes and features

- The Alliance 128 was designed for agricultural trailers in the field and on the road.
- The special tread pattern with shoulder lugs provides high traction in the field.
- The grooved tread pattern in the middle of the tread provides comfortable driving performance on roads during transport journeys.
- The tyre enables high loading capacity at low inflation pressure, optimum soil protection and low rolling resistance.
- Its strong nylon casing and rubber compound guarantee a long service life.



Technical Informations

Item number	15212674
EAN	7291050082136
Valid tyre size	800 / 35 - 22.5
LI / SI / PR	169 A8 / 162 D, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	128
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	132,68
Recommended rim size	28.00
Permitted rim size	24.00, 26.00
Maximum air pressure [bar].	2,60
Section width (mm)	800
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	523
Rolling circumference [mm].	3508
Tread depth (mm)	26,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	325
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A8	5800	40		2,60	
162 D	4750	65		2,60	