Bohnenkamp 📕 🛑 Moving Professionals

TYRES

Product group	Tyres	
Item number	15212705	
Valid tyre size	500 / 60 - 26.5	
LI / SI / PR	170 A2 / 163 A8, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestry 331	





Notes and features

- The Alliance Forestry 331 forest was developed for use • on modern harvesters and transport vehicles in the forestry sector.
- It is also highly-suitable for mobile excavators, wheel . loaders and dumpers working on difficult terrain.
- The tyre can also be used in agriculture for cultivating tough and abrasive surfaces.
- The tyre is characterised by high traction, low slip and low • fuel consumption.
- Its huge volume ensures low soil compaction and good • ride comfort in forestry and agricultural applications.
- Due to its strong nylon casing with steel belts, high undertread gauge, reinforced sidewalls and a sturdy rubber compound, the tyre is extremely robust and durable.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

item numberi5212705EAN29105014069Vald tyre size500 / 60 - 26.5L/ JS / PR700 / 70.2 / 163.8, 16 PRT/TT10.2 / 163.0, 16 PRBrandAliaceBrandNoTred patternForstry 31BreadyBoackType colourBiakBready16.0<		
NoteValid tyre size50/ 60 - 26.5LI / SI / PR10.42 / 163.48, 16 PRTLTTTLBrandAlianceBrandAlianceTread patternForestry 331AntistaticNoTyre colourBackECE 106ECE 106Nettogewicht [kg] (giltig)18.34Ansinam air pressure [bas]500Section width (mm)500Section width (scillig)120Brand120Antistig (SLR) [mm]500Solour Gamender Image500Section Scillig (SLR) [mm]500Subard Scillig (SLR) [mm]500Solour Gamender Image500Solour Gamender Image500Subard Scillig (SLR) [mm]500Solour Gamender Image500Solour Gamender Image	Item number	15212705
Li / Si / PRLi / Si / PRT/TTTLTuFrandAlianceAristaticForestry 331AntistaticNoECE regulation numberECE 106Nettogewicht [kg] (gültig)18,34Recommended rim size16.00Socion vidth (mm)50Stat radius (SLR) [mm]50Stat radius (SLR) [mm]50Reling circumference [mm]50Socion vidth (mm)50Socion vidth (mm)50 <t< th=""><th>EAN</th><th>7291050014069</th></t<>	EAN	7291050014069
TLTTITLTLBrandAlianceTread patternForesty 331AntistaticNoTyre colourBlackECE regulation numberECE 106Retogewich [kg] (gild)18,34Andication10.0Back10.0Colour10.0Back10.0 <t< th=""><th>Valid tyre size</th><th>500 / 60 - 26.5</th></t<>	Valid tyre size	500 / 60 - 26.5
BrandAlianceBrandAlianceTread patternForestry 331AntistaticNoAnistaticBackTyre colourBackBecomended rimsizeCE 106Notogewicht [kg] (gilit)18,34Atationamisrer source [the static	LI / SI / PR	170 A2 / 163 A8, 16 PR
Tread patternForestry 331.AntistaticNoTyre colourBlackECE regulation numberECE 106Nettogewicht [kg] (güttg)18,34Recommended rim size16.00Maximum air pressure [baz]4.00Section width (mm)200Outer diameter of tyre [mm]1270Rating (SLR) [mm]800Reling circumference [mm]820Tread depth (mm)900	TL/TT	TL
AntistaticNoAntistaticNoTyre colourBlackECE regulation numberECE 106Nettogewich [kg] (ülitig)18,34Recommended rim size16.00Maxinum air pressure [bai]00Section width (mm)50Stat. radius (SLR) [mm]50Radius (SLR) [mm]38.00Automatic methods39.00	Brand	Alliance
Tyre colourBlackECE regulation numberECE 106Nettogewicht [kg] (gültig)18.34Recommended rim size16.00Maxinum air pressure [ba]4.00Section width (mm)500Subschlein (SLR) [mm]500Stat. radius (SLR) [mm]380Rolling circumference [mm]39.0	Tread pattern	Forestry 331
FCE regulation numberECE 106Nettogewicht [kg] (gütt)g118,34Recommended rim size16.00Maximum air pressure [bar]4.00Section width (mm)500Outer diameter of tyre [mm]1270Stat. radius (SLR) [mm]3820Rolling circumfence [mm]39.0	Antistatic	No
Nettogewicht [kg] (gültig)18,34Recommended rim size16.00Maximum air pressure [ba]4,00Section width (mm)500Solo2170Stat. radius (SLR) [mm]590Rolling circumference [mm]38.00Subscieft (mm)39.00	Tyre colour	Black
Recommended rim sizei6.00Maxinum air pressure [bar]i0.0Section width (mm)i0.0Outer diameter of tyre [mm]i2.70Stat. radius (SLR) [mm]i3.0Rolling circumference [mm]i3.0	ECE regulation number	ECE 106
Maximum air pressure [bar] 4,00 Section width (mm) 500 Outer diameter of tyre [mm] 1270 Stat. radius (SLR) [mm] 590 Rolling circumference [mm] 3820 Tread depth (mm) 39,0	Nettogewicht [kg] (gültig)	118,34
Section width (mm)500Outer diameter of tyre [mm]1270Stat. radius (SLR) [mm]500Rolling circumference [mm]3820Tread depth (mm)30,0	Recommended rim size	16.00
Outer diameter of tyre [mm] 1270 Stat. radius (SLR) [mm] 590 Rolling circumference [mm] 3820 Tread depth (mm) 39,0	Maximum air pressure [bar].	4,00
Stat. radius (SLR) [mm] 590 Rolling circumference [mm] 3820 Tread depth (mm) 9,0	Section width (mm)	500
Rolling circumference [mm]. 3820 Tread depth (mm) 39,0	Outer diameter of tyre [mm].	1270
Tread depth (mm) 39,0	Stat. radius (SLR) [mm]	590
	Rolling circumference [mm].	3820
E-Ready No	Tread depth (mm)	39,0
	E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 A2	6000	10		4,00	
163 A8	4875	40		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.