

## TYRES

Product group	Tyres
Item number	15212744
Valid tyre size	600 / 55 - 26.5
LI / SI / PR	172 A2 / 165 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344



## Notes and features

- The Alliance Forestar 344 is a powerful forestry tyre for CTL machines.
- The steel-reinforced nylon casing, the special rubber compound, as well as the reinforced sidewalls, protect the tyre against punctures.
- The traction tread pattern with low-angled lugs provides excellent grip and good self-cleaning thanks to wide gaps between the lugs.
- Due to the close spacing of the lugs in the centre of the tread, the rolling resistance can be reduced on hard surfaces.
- Matching chains and ribbons are available on the market.

## Technical Informations

Item number	15212744
EAN	7291050042857
Valid tyre size	600 / 55 - 26.5
LI / SI / PR	172 A2 / 165 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	189,55
Recommended rim size	20.00
Maximum air pressure [bar].	5,00
Section width (mm)	620
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	619
Rolling circumference [mm].	4053
Tread depth (mm)	48,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A2	6300	10		5,00	
165 A8	5150	40		5,00	